MOORECONCRETE

LINTELS AND THRESHOLDS

Product Type	Height	Width	Increments	Max Length		
Dry Cast Lintels (Ideal for plastering over on blockwork houses)						
6" x 4"	145	95	150	2100		
9" x 4"	210	100	150	2700		
6" x 6"	140	140	300	3000		
Prestressed Lintels (Ideal for leaving exposed on brick/stonework houses)						
4" x 3"	100	65	150	2100		
6" x 4"	140	100	150	3600		
9" x 4"	215	100	300	4800		
Prestressed heads are fair faced on the top, bottom and one side as standard. Fair facing is available on both sides by request						

Padstones (For resting steel beams upon)						
6" x 4"	140	100	450	450		
9" x 4"	215	100	450	450		
Other sizes can be made to order (eg 9" x 6" or 9" x 9")						
Loading tables available on request						

Arched heads and corner padstones are also available on request.

Prestressed heads are suitable for multi-floor buildings according to loading tables. Please contact the building team for more information.

Door Thresholds

Also know as door blocks/slip-sills

Our 65mm wide x 140mm deep fair faced door blocks are the perfect size to set below your door way to create a threshold. It's thickness and width ensure a perfect fit with most door frames.











Width	Depth	Length		
65	140	1000		
		1200		
	•	1800		
		2000		
		2400		
Other lengths can be made to order				

Moore Concrete Products Ltd, Caherty House, 41 Woodside Road, Ballymena, County Antrim, Northern Ireland BT42 4QH

Tel: +44 (0) 28 2565 2566 **Fax**: +44 (0) 28 2565 8480

Web: www.moore-concrete.com Email: info@moore-concrete.com





